

# Silent Chain Specifications & Worksheet



Typical part description:

**SC408 SG 96P**

Chain type and pitch  
(SC for silent chain,  
EX for Excel)

Quantity per package in pitches or feet  
(i.e. "96 pitches" or 96 links)

Chain width  
(in 1/8's of inch, except for 3/16 pitch )

Guide location  
(SG for side guide, CG for center  
guide, MG for multiple guide)

Pitch	Standard chain widths*	Standard Chain Number	Standard Chain Width Descriptions**	Available in ASME silent chain	Available in Excel Series High Performance chain	Standard Connecting Link***
3/16	5/32" to 31/32"	03	05 - 31	Y	--	Rivet type
3/8	1/2" to	3	02 - 12	Y	Y	Drilled Pin
1/2	3/4 to 4"	4	03 - 16	Y	Y	Drilled Pin
3/4	1-1/2" to 5"	6	06 - 32	Y	Y	Drilled Pin
1	1" to 10"	8	08 - 40	Y	Y	Drilled Pin
1-1/2	3" to 12"	12	12 - 48	--	Y	Drilled Pin
2	3" to 18"	16	16 - 72	--	Y	Drilled Pin

\*Additional chain widths available on request

\*\* Chain width descriptions are expressed as 1/4's of an inch for all pitch sizes except 3/16" (SC03), which are expressed as 1/32's of an inch

\*\*\*Alternate and/or additional connecting links available on request

Standard Silent Chain    Chain Pitch \_\_\_\_\_     Side Guide     10 ft Box  
 Excel Series     Center Guide     50 ft Reel  
 High Performance Chain    Chain width \_\_\_\_\_     Multiple Guide     Other (Specify)

Number of strands: \_\_\_\_\_ Strand length: \_\_\_\_\_  Feet

List any special requirements: \_\_\_\_\_  Links

Crown Industrial Corp  
839 Rout 13, Cortland, NY 13045

(607) 299-4787

[www.crownindustrial.biz](http://www.crownindustrial.biz)

E-mail completed sheet to: [quotes@crownindustrial.biz](mailto:quotes@crownindustrial.biz)